


- ① FINISH GRADE.
- ② PLANT MATERIAL.
- ③ VALVE BOX.
- ④ APPROVED BACKFILL.
- ⑤ QUICK COUPLER KEY.
- ⑥ QUICK COUPLER HOSE SWIVEL.
- ⑦ QUICK COUPLER VALVE SEE PLAN LEGEND FOR SIZE.
- ⑧ LASCO STANDARD UNITIZED SWING JOINT, WITH; SNAP-LOK STABILIZER ELBOW OUTLET. NOTE: INLET IS ACME, OUTLET IS BRASS MIPT SNAP LOK.
- ⑨ 3/8" OR 1/2" x 24" REBAR (2) REQUIRED.
- ⑩ MAINLINE PIPE PVC, SEE LEGEND FOR TYPE, SIZE PER PLAN.
- ⑪ 1" PVC PIPE STABILIZER.
- ⑫ LASCO ACME SERVICE TEE OR ELBOW. (SIZE PER PLAN).

LASCO SWING JOINT WITH SNAP-LOK, 1½" ACME INLET.

- ¾" Q.C.V., with LASCO 1" Swing Joint, 1½" ACME Inlet x ¾" SNAP-LOC Brass MIPT Outlet, Model #G1MT-212.
- 1" Q.C.V., with LASCO 1" Swing Joint, 1½" ACME Inlet x 1" SNAP-LOC Brass MIPT Outlet, Model #G1MS-212.
- 1½" Q.C.V., With LASCO 1½" Swing Joint, 1½" ACME Inlet x 1½" SNAP-LOC Brass MIPT Outlet, Model #G3MS-212.



LASCO SWING JOINT FOR Q.C.V., ACME X SNAP-LOC

N.T.S.

DETAIL-FILE