



- ① FINISHED GRADE.
- ② SPRAY/ROTARY/ROTOR SPRINKLER HEAD, OVER 4.0 G.P.M.
- ③ LASCO SWIVEL JOINT – PUT A "X" IN THE BOX TO DETERMINE SIZE AND INLET/OUTLET ENDS WANTED.
- ④ LATERAL PVC PIPE.
- ⑤ APPROVED BACKFILL.
- ⑥ LASCO SERVICE TEE OR ELBOW, SCH40. (SIZE PER PLAN), SIZE TEE/ELBOW FIPT OUTLET BASED ON MIPT INLET SIZE OF THE SWING JOINT.

SPRAY OR ROTARY HEAD OVER 4.0 G.P.M. LASCO SWIVEL JOINTS

- ¾" Lasco Swivel Joint for Spray heads over 4.0 g.p.m., ¾" MIPT Inlet x ½" MIPT Outlet, Part #T7532-212, Standard 12" Lay Length.

ROTOR HEAD OVER 4.0 G.P.M. LASCO SWIVEL JOINTS

- ¾" Lasco Swivel Joint for Rotor heads over 4.0 g.p.m., ¾" MIPT Inlet x ¾" MIPT Outlet, Part #T732-212, Standard 12" Lay Length.

IF A DIFFERENT LAY LENGTH ARM IS WANTED INSTEAD OF 2 MODEL'S SHOWN ABOVE WITH 12" LAY LENGTH, PLEASE SELECT THE LENGTH BELOW, JUST CHANGE THE LAST 3 DIGITS OF PART #;

- Lay Length Arm 8" (Option), #TXXXX-208.
- Lay Length Arm 15" (Option), #TXXXX-215.
- Lay Length Arm 19" (Option), #TXXXX-219.

00 LASCO SWIVEL JOINTS, W/1/2 & 3/4" OUTLETS

N.T.S. 1/2" AND 3/4" SPRINKLER HEADS W/FLOW OVER 4 G.P.M.

DETAIL-FILE