

SUBMITTAL SHEET

THRUST PLUG



JOB NAME	
JOB LOCATION	
ENGINEER	
CONTRACTOR	
TAG	
PO NUMBER	
REPRESENTATIVE	
WHOLESALE DISTRIBUTOR	

- Attached to a compatible Tap't™ Coupling for secure end-of-line connections.
- Size recommendation of Thrust Block (concrete pad) is embossed on each Thrust Plug.
- ASTM D-1784
- ASTM F-1970

SPECIFICATIONS:

Maximum Working Pressure: 315 psi @ 73 deg F

ASTM D1784 - Rigid Poly (Vinyl Chloride) (PVC) Compounds and Chlorinated Poly Vinyl Chloride (CPVC) Compounds

ASTM D1970 - for Special Engineered Fittings, Appurtenances or Valves for use in Poly (Vinyl Chloride) (PVC)

SUGGESTED SPECIFICATIONS:

Thrust Plugs & gasketed Tap't Coupling service fittings as manufactured by LASCO Fittings, Inc. shall be utilized where indicated on plan. Thrust plugs shall be installed into the corresponding size of LASCO Fittings, Inc. Tap't Couplings, molded of rigid polyvinyl chloride (PVC), Type 1 cell classification 1254 per ASTM standard D- 1784, and meet ASTM standard F-1970 for Special Engineered Fittings, Appurtenances or Valves for use in Poly (Vinyl Chloride) (PVC). Thrust blocks shall be installed behind the Thrust Plugs and meet the recommended size embossed on the surface of the Thrust Plug.

MATERIALS:

PVC Type 1 Cell Classification 12454-B

HOW TO ORDER:

PART #	SIZE (in)	Recommended Thrust Block Size
349-020	2	19 inches x 19 inches

WARRANTY:

Five Year Limited Performance Warranty

LASCO Fittings, Inc. products are warranted to be free from manufacturing defects in materials and workmanship. They are warranted against rot, rust, and electrolytic corrosion for a period of five years from date of installation. If LASCO products prove defective due to manufacturing defects in material or workmanship during that period, the manufacturer will provide new replacement units of the same type and size. No remedy will be granted under this warranty if LASCO products are not used strictly in accordance with LASCO's directions with respect to use and storage or if the products have been modified in any way.

THE MANUFACTURER'S LIABILITY UNDER EXPRESSED OR IMPLIED WARRANTY OR FOR ANY REASON IS LIMITED TO FURNISHING REPLACEMENT UNITS OR GRANTING A CREDIT FOR DEFECTIVE UNITS. NO LABOR EXPENSE OR CONSEQUENTIAL DAMAGES WILL BE PAID BY LASCO. THIS WARRANTY IS IN LIEU OF ALL OTHER GUARANTEES AND WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PURPOSE, EXCEPT FOR ANY WARRANTIES IMPLIED BY LAW FOR NONCOMMERCIAL CONSUMERS. ANY SUCH WARRANTIES ARE LIMITED TO THE DURATION OF THIS WRITTE WARRANTY.

DO NOT USE LASCO FITTINGS FOR COMPRESSED AIR OR GASES.
DO NOT TEST PVC PIPING SYSTEMS WITH COMPRESSED AIR OR GASES.
DO NOT USE FITTINGS WITH LIQUIDS NOT RECOMMENDED BY LASCO.
MODIFICATIONS OF FITTINGS VOIDS THE WARRANTY.

414 Morgan Street • Brownsville, TN 38012
(731) 772-3180 | www.lascofittings.com